



赣工机械设备科技(东莞)有限公司
TEL: 15920631511

PART NUMBER: STD124
REVISION: K

Product Specifications

Model Number	MAX. PRESS.		MAX. SPEED	HP	kW	Net Wt.	
	bar.	PSI				lbs.	kg
4AM-NRV-50C	7.0	100	3,000 RPM	1.7	1.25	11	5.0
4AM-NRV-50L	7.0	100	3,000 RPM	1.7	1.25	11	5.0
* 4AM-NRV-50M	7.0	100	3,000 RPM	1.7	1.25	11	5.0
4AM-NRV-70C	7.0	100	3,000 RPM	1.7	1.25	11	5.0

TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

DIMENSIONS ARE FOR REFERENCE ONLY UNLESS OTHERWISE TOLERANCED.

SOUND LEVEL 87 dB(A) MAX.
NORMAL AMBIENT +1°C. - 120°C.
RELATIVE HUMIDITY 0% - 100%
ENVIRONMENT HAZARDOUS AMBIENT COMBUSTIBLE GAS AND DUST +1°C TO +40°C

CONFORMS TO EUROPEAN STANDARD EN13463-1 NON-ELECTRICAL EQUIPMENT FOR EXPLOSIVE ATMOSPHERES GROUP II CAT 2 (GAS & DUST), PROTECTED BY CONSTRUCTION (SURFACE TEMP. RATED 135°C).

